






HydrauPack 450

Features


- Diesel driven hydraulic power unit
- Pump flow electronically controlled from 0-100%
- Open hydraulic circuit with electronic pressure and flow control
- Intelligent electronic control system
- Sound-insulated
- Electric transfer pump to fill hydraulic tank

Benefits

- 24/7** 24/7 (de)mobilisation, installation and commissioning
-  Maintenance during the project

-  Guaranteed flexibility and high availability
-  Clear budget and manageable costs

Specifications HP450



Max. working pressure	350 bar
Max. output flow	660 liter/min
Total engine power	391 kW @ 1800 rpm (25 °C)
Cooling capacity water/oil	90 kW @ dT = 25 °C
Hydraulic fluid	H(V)LP ISO VG 46
Connection DOP Pressure (P)	Stucchi VOF200 2" BSP N (Nipple)
Connection DOP Tank (T)	Stucchi VOF200 2" BSP C (Coupler)
Connection DOP Drain (L)	Stucchi VOF100 1" BSP C (Coupler)
Connection Cutter Forward (A)	Stucchi VOF100 1" BSP N (Nipple)
Connection Cutter Reverse (B)	Stucchi VOF100 1" BSP N (Coupler)
Connection Cutter Drain (L)	Snap-tite VHC8-8RP (Coupler)