

Hydrau**vision**



HydrauPack 20E Mobile H.P.U.

Technical Specification

Max. working pressure	: 260 bar
Max. output flow	: 36 liter/min. @ 50 Hz : 44 liter/min. @ 60 Hz
Electric motor power	: 18,5 kW @ 400VAC (50Hz) : 22 kW @ 440VAC (60Hz)
Operational temperature	: -20 to 50 °C
Hydraulic fluid	: H(V)LP ISO VG 46 (or other on request)
Hydraulic manifold block operated	: 3 sections PVG32, proportional, manual : with 1 section electrical on/off operation : 7 pressure gauges : manual control pump pressure setting
Overall length	: 925 mm
Overall width	: 1290 mm
Overall height	: 1660 mm
Total weight excl. / incl. oil	: 450 kg / 710 kg
Hydraulic oil tank capacity	: 300 liter
Power supply nominal	: 400 VAC (50Hz)-63A (3P +E) : 440 VAC (60Hz)-63A (3P +E)
Fluid connections	
Pressure (3x A & B)	: 16S acc. EN / ISO 8434
Drain (D)	: 25S acc. EN / ISO 8434
Tank Drain (TD)	: 16S acc. EN / ISO 8434

Detailed specifications : on request

Benefits

- Open hydraulic circuit with pressure and load sense control
- Transportable
- Easy to operate
- Including filtration, low oil level and high temperature alarm
- Including emergency stop and phase control

Scope of Supply

Included:

- Power connector on unit: 63A-6h, 5-pole
- Controller settings to customers specifications
- User manual

Excluded:

- Hydraulic hoses
- Electric power connection cable
- Transport and installation
- Lifting frame

Above mentioned items can be included on request.

All performance data and specifications mentioned in this document are guidelines. Due to operational and environmental influences performance data may vary. All products are subject to continuous review. Hydrauvision reserves the right to change specification without prior notice.

Revision : 01
Date : 27-06-2014

Mobile electric-driven Hydraulic Power Unit with a main power of 18,5 kW @ 400VAC-50Hz or 22 kW @ 440VAC-60Hz.

The HydrauPack 20E is provided with a pressure and load sense controlled axial piston pump to supply 3 proportional valves.
System is easy to operate and to monitor.

The HydrauPack 20E is assembled on wheels and provided with a push bar, lashing lugs and integrated forklift-trays to ensure easy handling.

In case the unit must be lifted by crane, a lifting frame can be provided.

Hydrau**vision**



www.hydrauvision.com
+31 (0) 88 57 47 000

HydrauRent[®]
HYDRAULIC RENTAL EQUIPMENT

