Hydrauvision



Diesel-driven Hydraulic Power Unit with an engine output power of 34 kW.

The complete unit is integrated in a frame. In this frame, a hydraulic driven oil- cooler ensures reliable performance under hot conditions.

The sound-insulated HydrauPack 35 is provided with lifting lugs and integrated forklift trays to ensure easy handling.

HydrauPack 35

Technical Specification

Max. working pressure : 210 bar
Max. output flow : 80 liter/min.
Total engine power : 34 kW (25°C)
Effective hydraulic power
Operational temperature : -15 .. +55 °C

Overall length : 1510 mm
Overall width : 1010 mm
Overall height : 1615 mm
Total weight excl. fluids : 915 kg
Hydraulic oil tank capacity : 70 liter
Fuel tank capacity : 130 liter

Fluid connections:

Pressure : 25S
 Return : 42L
 Drain : 28L
 Loadsense : 12S

Benefits

The following hydraulic controls and systems are possible:

- Open circuit.
- Pressure control.
- Load sensing control.

Integrated hydraulic oil cooler.

Scope of Supply

Included:

- Controller settings to customers specifications.
- User manual.

Excluded:

- Hydraulic hoses.
- Transport and installation.

Above mentioned items can be included on request.

Hydrauvision

