

# Hydrau**vision**



## HydrauPack 45

### Technical Specification

Max. working pressure	: 300 bar
Max. output flow	: 120 liter/min. @ 3000 rpm
Total engine power	: 45 kW (25°C)
Operational temperature	: -15.. 38 °C

Overall length	: 1500 mm
Overall width	: 1000 mm
Overall height to top of exhaust	: 1760 mm
Total weight excl. / incl. fluids	: 1300 kg / 1725 kg
Hydraulic oil tank capacity	: 230 liter
Fuel tank capacity	: 240 liter

Fluid connections:	
- Pressure	: 30S
- Return	: 42L
- Leak	: 28L
- Load sense	: 12S
- Flush	: 16S
- Tank drain	: 28L

### Benefits

Following hydraulic controls and systems are possible:

- Open circuit.
- Pressure control.
- Load sensing control, with external connection.
- Horse power compensation.
- Flushing connection for separate low pressure flushing.
- Integrated hydraulic oil circulation cooler.

### Scope of Supply

Included:

- Controller settings to customers specifications.
- Certified shackles.
- User manual.

Excluded:

- Hydraulic hoses.
- Transport and installation.

Above mentioned items can be included on request.



Stackable diesel-driven Hydraulic Power Unit with a main power of 45 kW @ 3000 rpm.

The HydrauPack 45 can be combined with one or more other HydrauPack 45 units in order to obtain a higher output flow.

The HydrauPack 45 is provided with lifting lugs and integrated forklift-trays to ensure easy handling.

# Hydrau**vision**

