

# Hydrau**vision**



Diesel-driven Hydraulic Power Unit with a maximum engine power output of 2 x 280 kW, combined engine power output is 560 kW.

The hydraulic output of 2 x 205 kW can be combined in one connection, but also has 2 separate connections with quick connectors.

Two separate flush connections for external equipment are available if required.

The HydrauPack 560 is assembled in a Lloyd's Register certified 15 feet offshore high cube container according D.N.V. rules 2.7-1 and EN 12079 including rigging.

The container is provided with both 4 lifting points and integrated forklift-trays to ensure easy handling.

## HydrauPack 560 15 ft. HC container

### Technical Specification

Max. working pressure	: 350 bar
Max. output flow	: 2 x 450 liter/min (up to 275 bar)
Max. output flow @ 350 bar	: 2 x 350 liter/min.
Total engine power	: 2 x 280 kW @ 1800 rpm (25°C)
Effective hydraulic power	: 2 x 205 kW (25°C) approx.
Flush capacity	: 2 x 45 liter/min @ 30 bar
Cooling capacity air / oil	: 2 x 100 kw @ dT= 25 °C
Operational temperature	: -20 up to 50 °C
Hydraulic fluid	: H(V)L/ISO VG 46, 68 (or other on request)

Overall length	: 4630 mm
Overall width	: 2440 mm
Overall height	: 2900 mm (excl. exhaust pipe)
Overall height	: 3074 mm (incl. exhaust pipe)
Total weight excl. / incl. fluids:	12900 kg / 15390 kg
Hydraulic oil tank capacity	: 1800 liter
Fuel tank capacity	: 2 x 500 liter

Fluid connections	
Pressure (P)	: 2 pcs Q.C.Snap-tite series 75, 2" (male)
Return oil (T)	: 3 pcs Q.C. Tema T20020 Male 2"
Drain (D)	: Q.C. Tema T15020, 1½" (male)
Filling point	: Q.C. flat face acc. ISO 16028, ½" (male)
Load sense (LS)	: G ½" BSP (plugged), 2 pcs
Flush (F)	: G 1" BSP (plugged), 2 pcs

Detailed specifications : on request

### Benefits

- Intelligent electronic control system
- Connection for electric remote control by Renter
- Offshore certified 15 ft. high cube container and rigging acc. DNV 2.7-1 CSC and EN12079
- Air cooling systems
- Flush connections for external equipment
- Open hydraulic circuit with pressure cut-off and load sense control
- For transport purposes exhaust pipe can be replaced by blinding plate and stored in HPU

### Scope of Supply

Included:

- Controller settings to customers specifications
- User manual

Excluded:

- Hydraulic hoses with counter quick connectors
- Remote control
- Transport

Above mentioned items can be included on request.

All performance data and specifications mentioned in this document are guidelines. Due to operational and environmental influences performance data may vary. All products are subject to continuous review. Hydrau**vision** reserves the right to change specification without prior notice.

Revision : 01  
Date : 19-03-2018

# Hydrau**vision**



[www.hydrau\*\*vision\*\*.com](http://www.hydrau<b>vision</b>.com)  
+31 88 57 47 000

**HydrauRent**<sup>®</sup>  
HYDRAULIC RENTAL EQUIPMENT

