

Hydrau**vision**



HydrauPack 65

Technical Specification

Max. working pressure	: 320 bar
Max. output flow	: 150 liter/min. (variable up to 210 bar)
Max. output flow @ 320 bar	: 100 liter/min.
Total engine power	: 64kW @ 2300 rpm (25 °C)
Effective hydraulic power	: approx. 59 kW (25 °C)
Operational temperature	: -15 up to 55 °C
Hydraulic fluid	: H(V)LP ISO VG 46, 68 (or other on request)

Overall length	: 2580 mm
Overall width	: 1340 mm
Overall height	: 2090 mm
Total weight excl. / incl. fluids	: 2345 kg / 2650 kg
Hydraulic oil tank capacity	: 200 liter
Fuel tank capacity	: 140 liter

Fluid connections:	
- Pressure (P)	: 30S
- Return (T)	: 35 L
- Load sense (LS)	: 10S
- A + B (6 pcs.)	: 20S

Benefits

The following hydraulic controls and systems are possible:

- Open circuit
- Flow control
- Pressure control
- Load sensing control
- Optional remote control
- Integrated hydraulic oil cooler

Scope of Supply

Included:

- Controller settings to customers specifications
- User manual
- Integrated 6-fold proportional valve, 65 l/min. each valve with connections 20S

Excluded:

- Hydraulic hoses.
- Remote control.
- Spark arrestor.
- Transport and installation.

Above mentioned items can be included on request.

All performance data and specifications mentioned in this document are guidelines. Due to operational and environmental influences performance data may vary. All products are subject to continuous review. Hydrauvision reserves the right to change specification without prior notice.

Revision :16
Date : 10-04-2017



Diesel-driven Hydraulic Power Unit with an engine output power of 64 kW. The HydrauPack 65 is provide with a 6-fold electric operated proportional valve, with manual override function. Remote control of two of these valves is possible.

The sound-insulated HydrauPack 65 is provided with lifting lugs to ensure easy handling.

Hydrau**vision**



www.hydrauvision.com
+31 (0) 88 57 47 000

HydrauRent[®]
HYDRAULIC RENTAL EQUIPMENT

