

Hydrau**vision**



HydrauPack 15E M

Technical Specification

Max. working pressure	: 320 bar (up to 28 l/min.)
Max. output flow	: 66 liter/min. (up to 135 bar)
Electric motor power	: 15 kW @ 50 Hz
Operational temperature	: -15 .. 55 °C

Length	: 1460 mm
Width	: 870 mm
Height	: 1820 mm
Total weight excl. fluids	: 600 kg
Hydraulic oil tank capacity	: 200 liter

Power supply	: 400VAC-50Hz 63 Amp.
--------------	-----------------------

Benefits

The following hydraulic control options are possible:

- Open circuit.
- Flow control.
- Pressure control.
- Load sensing control.

Scope of Supply

Included:

- Controller settings to customers specifications.
- User manual.
(integrated phase reversal)
- Integrated 2-fold valve with open center. Manual operation.
- Integrated phase sequence sensor.

Excluded:

- Hydraulic hoses.
- Power supply cable CEE 63A 5P.
- Transport and installation.
- Wired remote control

Above mentioned items can be included on request.



The HydrauPack 15E M is a mobile hydraulic power unit, provided with a double proportional directional control valve. The proportional control valve can be operated manually or remote controlled. The transport wheels makes it possible to move around easily to the working area. The HPU is especially suitable for testing purposes for hydraulic systems.

Hydrau**vision**



www.hydrauvision.com
+31 (0) 88 57 47 000

HydrauRent[®]
HYDRAULIC RENTAL EQUIPMENT

All performance data and specifications mentioned in this document are guidelines. Due to operational and environmental influences performance data may vary. All products are subject to continuous review. Hydrauvision reserves the right to change specification without prior notice.

Revision : 12
Date : 12-12-2016